

GÖLZ®



**Hand-Held Power Tools
for Diamond Tool Operation**

www.golzgroup.com

Robust and powerful - perfect for small grinding and polishing requirements.

Easy polishing - grinding - cleaning

Perfect surface preparation

Features

- Softstart and surface speed control
- Thermal overload protection shown by LED lights
- 125 mm dust collector cover, front can be opened to operate direct against a wall
- 35 mm vacuum hose connector
- Handles adjustable for your comfort
- Carrying case inclusive



Specifications	GÖLZ SM125
Motor	230 V, 50 - 60 Hz
Power	1,8 kW
RPM	10.000 min ⁻¹
Cup Grinder Ø	125 mm
Arbor hole Ø	22,23 mm
Soft-Start	yes
Protection class	2
Weight	5,4 kg
Order number	SM 125

Accessories	Order number
Dry Vac Vibra 125	0284 810 3000

Powerful Wall Chaser - Designed for your safety and comfort.

Operates 2 diamond blades up to a max. cutting width of 46 mm and a max. cutting depth of 45 mm.

Quick and easy to use in

- Sandstone
- Soft bricks
- Poroton
- Hard bricks
- Limestone
- Clinker
- Concrete

Features

- Softstart electronic
- Thermal overload protection
- Overload LED lights
- Easy cutting depth adjustment
- Easy tool change
- 35 mm vacuum hose connector
- Carrying case inclusive

Advantages

- Cuts 15mm close to a wall
- Ergonomical Handles
- Easy handling
- Steppless cutting depth adjustment
- Easy handling by big switches and buttons
- Almost dust free



Specifications	GÖLZ SF150
Operation	Dry only
Motor	230 V, 50 Hz
Power	2,3 kW
RPM	4.300 min ⁻¹
max. Blade Ø	150 mm
Arbor hole Ø	22,23 mm
Max cutting depth	45 mm
Max cutting width	46 mm
Weight	5,8 kg
Order number (without diamondblade)	SF 150

Accessories	Order number
Dry Vac Vibra 125	0284 810 3000

Electric Cut Off Saw ES350

Electrical Cut Off Saw for wet and dry operation - Vac-adaptor for slurry and dust control - the allround saw for most of your sawing requirements up to a cutting depth of 130 mm (5 inch)

Powerful 2,7 kW Electric-Cut Off Saw - 350 mm (14 inch) blade and blade guard with integrated vac-adaptor. The anti-clockwise rotating blade guarantees best dust and slurry control by connecting a vacuum cleaner.

Quick and easy to use in

- All kinds of openings in concrete or brick walls
- Cutting pipes, concrete, stone, clinker and brick

Features

- 2,7 kW electric motor with soft start electronic
- Thermal overload protection
- Easy cutting depth adjustment
- Easy tool change
- 35 mm vacuum hose connector
- Adjustable blade guard and handles
- Easy to operate by extra wide guiding wheels



Specifications	GÖLZ ES350
Operation	Dry and Wet
Motor	230 V, 50 Hz
Power	2,7 kW
RPM	2.200 min ⁻¹
max. Blade Ø	350 mm
Arbor hole Ø	25,4 mm
Max cutting depth	130 mm
Weight	12,5 kg
Order number	0295 150 1300

Accessories	Order number
Cutting depth limiter	0295 150 1310
Close to wall cutting adapter	0295 150 1311

Hand Held Core Drilling Machines



Single Speed Dry Drilling Hand Held Core Drill.
Dry drilling with and without dust collection for
switches and junction boxes

- Single speed drill for holes up to 160 mm
- No vibrations, no impact drilling
- Dry drilling in soft bricks, blocks and poroton, porous concrete, sand-lime bricks
- Thermal overload protection
- Accessories: Dry core bits, Dust collector, see Diamond tools catalogue (page 29)
- Carrying Case inclusive



Specifications	GÖLZ TB10S
Operation	Dry
Style	D-handle
Motor	Single phase, 230 V, 50 Hz
Power	1,8 kW (1,2 kW)
RPM	1200 min ⁻¹
Gears	1
Bit-ø in Brickwork (Dry)	Ø up to 160 mm
Drill bit connection	M18 male
Water connection	---
Ring collar Ø	53 mm
Dimensions (LxWxH)	460x95x320 mm
Weight	5,7 kg
Order number	0295 007 6050

2-Speed Heavy Duty Hand Held Core Drill.
Compact Core Drill for anchor and installation holes

- 2-Speed Gearbox
- Drill Bit connection 1 1/4" UNC + R 1/2" (FB23) or R1/2" (FB25)
- PRCD integrated in the power cord
- Softstart and thermal overload protection
- FB23S/FB23P - wet & dry use up to Ø 200 mm
- FB25P- wet use, up to Ø 70 mm
- Horizontal & Vertical Bubble Levels
- Toolset SW32 & SW41 inclusive
- Carrying Case inclusive



Specifications	GÖLZ FB23S	GÖLZ FB23P	GÖLZ FB25P
Operation	Wet & Dry		Wet
Style	D-handle	Pistol-handle	
Motor	Single phase, 230 V, 50 Hz		
Power	2,2 kW (1,5 kW)		
RPM	520/1400 min ⁻¹		1400/2900 min ⁻¹
Gears	2		
Bit-ø in Concrete (Wet)	10 - 110 mm – Hand held 10 - 200 mm – Stand mounted		10 - 70 mm - Hand held 10 - 70 mm - Stand mounted
Bit-ø in Brickwork (Dry)	20 - 200 mm - Hand held, (Optional dust collector)		
Drill bit connection	1¼"UNC + R½"		R½"
Water connection	Gardena		
Ring collar Ø	60 mm		
Dimensions (LxWxH)	547x150x100 mm	396x100x295 mm	337x100x295 mm
Weight	5,9 kg	5,9 kg	5,6 kg
Order number	0295 007 5063	0295 007 5020	0295 007 5025

Accessories	Order number
Drill Stand DS160S (up to Ø 162 mm)	0295 110 9010
Drill Stand KB125 (up to Ø 200 mm)	0295 125 6000



3-Speed Heavy Duty Hand Held Core Drill.
Powerful core drill is full in metal housing for hand held or drill stand operation

- 3-Speed Gearbox
- Drill Bit connection 1 1/4" UNC + R 1/2"
- PRCD integrated in the power cord
- Softstart and thermal overload protection
- Wet & dry use up to Ø 200mm
- Horizontal & Vertical Bubble Levels
- Toolset SW32 & SW41 inclusive
- Carrying Case inclusive



Specifications	GÖLZ FB33PNT	GÖLZ FB33SNT
Operation	Wet & Dry	
Style	Pistol-handle	D-handle
Motor	Single phase, 230 V, 50 Hz	
Power	2,2 kW (1,5 kW)	
RPM	520/1400/2900 min ⁻¹	
Gears	3	
Bit-ø in Concrete (Wet)	20 - 110 mm - Hand held 20 - 200 mm - Stand mounted	
Bit-ø in Brickwork (Dry)	20 - 200 mm - Hand held Dust collector integrated	
Drill bit connection	1 1/4" UNC + R1/2"	
Water connection	Geka-coupling / Gardena	
Ring collar Ø	60 mm	
Dimensions (LxWxH)	440x100x285 mm	562x100x150 mm
Weight	6,5 kg	
Order number	0295 007 5082	0295 007 5065



Accessories	Order number
Drill Stand DS160S (up to Ø 162 mm)	0295 110 9010
Drill Stand KB125 (up to Ø 200 mm)	0295 125 6000

3-Speed Hand Held Core Drill.
For hand held or drill stand operation

- 3-Speed Gearbox
- Drill Bit connection 1 1/4" UNC + R 1/2"
- PRCD integrated in the power cord
- Thermal overload protection
- Wet & Dry use in Concrete and Brickwork
- Horizontal & Vertical Bubble Levels
- Toolset SW32 & SW41 inclusive



Specifications	GÖLZ FB20P
Operation	Wet & Dry
Style	Pistol-handle
Motor	Single phase, 230 V, 50 Hz
Power	2,2 kW (1,5 kW)
RPM	450/1200/2500 min ⁻¹
Gears	3
Bit-ø in Concrete (Wet)	20 - 110 mm - Hand held 20 - 200 mm - Stand mounted
Bit-ø in Brickwork (Dry)	20 - 200 mm - Hand held
Drill bit connection	1 1/4" UNC + R1/2"
Water connection	Gardena
Ring collar Ø	60 mm
Dimensions (LxWxH)	432 x 119 x 272 mm
Weight	6,7 kg
Order number	0295 007 5080

Accessories	Order number
Carrying Case	B802223
Drill Stand DS160S (up to Ø 162 mm)	0295 110 9010
Drill Stand KB125 (up to Ø 200 mm)	0295 125 6000





GÖLZ® - Group

GÖLZ GmbH

Dommersbach 51 | 53940 Hellenthal

Telefon +49 2482 12-0 | Fax +49 2482 12-222

info@goelz.de | www.goelz.de

ÖSTERREICH

Gölz Ges.m.b.H.

Samstr. 52 | A-5020 Salzburg

Telefon +43 662 438175 | Fax +43 662 430734

info@goelz.at | www.goelz.at

FRANKREICH

Gölz S.A.S.

1, rue de la Mairie | F-67370 Berstett

Telefon +33 3 88 59 43 00 | Fax +33 3 88 59 47 77

info@golz.fr | www.golz.fr

GROSSBRITANNIEN

Golz (UK) Ltd.

Unit A5 | Springhead, Enterprise Park

Northfleet | Kent DA 11 8HB

Telefon +44 1 474 321 679 | Fax +44 1 474 321 477

info@goelz.co.uk | www.golzuk.com

BENELUX

Gölz Benelux N.V. Belgien

Eupener Straße 61 | B-4731 Raeren-Eynatten

Telefon +32 87 55 23 49 | Fax +32 13 78 33 28

benelux@goelz.de | www.golzgroup.com

USA

Golz L.L.C.

5860 East Osage Ridge Lane | Columbia MO 65203-6018

info@golzusa.com | www.golzgroup.com



Your GÖLZ dealer

