

# MB500 / MB650 Band Saw

Sturdy band saw in painted steel for dry cutting of cellular concrete and Poroton blocks

Masonry Saws



Cutting Height 50/65 cm



Angle Guide (0-90°)



Push-Handle Worktop



Double Hinging Worktop

## Cutting Length 655 mm (26") Cutting Height 500 mm (20") or 650 mm (26")

Leicht, schnell und präzise zum Trocken-Sägen von

- Poroton
- Porenbeton
- Gasbeton
- Kalksandstein
- Hohlblockziegel

- 230V electrical connection - usable everywhere
- Transportwheels included
- Easy building and handle
- Very precise vertical and longitudinal cutting
- Equipped with automatic switch off system when the bench end its run
- Tungsten Carbide upper and lower blade guides
- Lifting eye
- Aluminum cutting table, tiltable for transport



Lifting Eye



Saw Band Tensioning



Transport Bar (Accessories)



Specifications	GÖLZ MB500	GÖLZ MB650
Power Engine	2,2 Kw, 230 V, 50 Hz	2,2 Kw, 230 V, 50 Hz
Max. Cutting Height	500 mm	650 mm
Max. Cutting Length	655 mm	655 mm
Band Saw Length	3.850 mm	4.150 mm
Worktop Dimension (W x L)	710 x 1.000 mm	710 x 1.000 mm
Worktop Hight	780 mm	780 mm
Wheels Diameter	160 mm	160 mm
Dimensions (LxW x H)	1.000x940x1.860 mm	1.000x940x2.010 mm
Weight	174 kg (382 lbs)	180 kg (396 lbs)
<b>Order number</b>	<b>0282 950 1000</b>	<b>0282 950 2000</b>

Accessories	Order number
Transport Bar	<b>0282 950 0900</b>

Sägeblatt für	MB500	MB650
Standard Gasbeton	WIDA3850x27	WIDA4150x27
Universal Gasbeton / Poroton	WIDA3850x34	WIDA4150x34
Premium Poroton / Bricks	WIDA3850x341	WIDA4150x341